

Linseed Oil

Double boiled linseed oil

Linseed Oil is a natural oil used for interior wood finishing. It offers a satin finish resistant to water and alcohol. Over the years, when applied to light-colored wood, Linseed Oil gives wood an amber tone.

Preparation

Sand evenly with 120 grit sandpaper and dust off the surface. Stir the content thoroughly. Dilute with 30% oil thinner.

Application

Apply a generous oil coat with a stain pad, a cotton rag or a stain applicator. After 15 to 20 minutes, remove any excess oil by rubbing the surface with a cotton rag.

Number of coat

3 coats

Drying time

- First coat : 12 hours
- Other coats : 24 hours
- Utilization : 2 days
- First damp cleaning : 14 days

Covering

120 to 230 sq ft / L

Concrete, slate, clay

Finico Linseed oil can also be used to seal concrete, slate or clay. The application is the same as for wood. The number of coats required may vary depending on the porosity of the surface.

Tools cleaning

Oil thinner

Compatibility

Compatible with most milk paints, chalk paints, mineral paints, stains and varnishes.

It's strongly recommended reading carefully the technical sheet of the product and making prior test to ensure the propriety and compatibility of the products



- Creation of an amber patina over time
- Water resistant
- Alcohol resistant
- Easy application
- Interior finishing

Project types

Interior structures, Floors, Paneling, Furniture, Woodwork

Surface types

Wood, Cork, Stone, Concrete

Composition

Double-boiled pale linseed oil

VOC

0 g / L

Durability

- Interior structures and woodwork: 3 to 7 years
- Floors: 1 to 3 years
- Paneling: 1 to 5 years
- Furniture: 1 to 3 years

Application tools

- Stain Pad
- Stain Applicator
- Cotton Rag
- Pinceau

Residues Disposal

Consult your municipality for proper disposal procedure of this product residues.

Caution

Ventilate well. Wear protective gloves and safety glasses.

DANGER OF COMBUSTION Keep out of reach of children. Materials such as rags used with this product may begin to burn by themselves. After use, put rags in water or lay flat to dry, then discard.

Warranty

Tembi products guarantee the quality of its products. They comply with the description given in the data sheets and proper labels for their intended use, in accordance with the instructions indicated by the company. However, since the manufacturer has no control over the circumstances, methods and usage conditions, this warranty covers only the high quality of Finico products

Maintenance

Clean with a oil based soap. After 1 to 3 years, if the finish becomes dull, apply one coat of oil and wipe off any excess.

Color

Colorless

Aspect

Viscous liquid slightly amber

Sizes

- 946 ml
- 3.78 L
- 18.9 L

Storage

Keep in an hermetic container at room temperature.

Conservation

5 years

Origin

U.S.A